

# Objet<sup>®</sup> 260 Connex3<sup>™</sup>



## Unleash your creativity with PolyJet's most advanced 3D printing.

Inspire your design process with the Objet260 Connex3 multi-material 3D printer. The Connex3 empowers you to 3D print brilliantly colored prototypes to fit your application needs. Get unmatched design freedom with a wide range of material properties, from rigid to flexible, transparent to opaque, neutral to vibrant, standard to bio-compatible and durable to high temperature. With Connex3, incorporate dozens of colors into one prototype, from vivid opaque to stained-glass-like translucent, with hundreds of blended hues in between.

Backed by triple-jetting technology, the Objet260 Connex3 delivers maximum versatility for your office. Combine up to three base resins in a single build to create models with a variety of Digital Materials, with minimal post-processing efforts. Produce models as large as 255 x 252 x 200 mm (10.0 x 9.9 x 7.9 in.) with impressive detail and ultra-fine accuracy — quickly and easily.

Learn more about the  
Objet260 Connex3  
at [stratasys.com](http://stratasys.com)



## 3D Printer Specifications

<b>Model Materials</b>	Rigid Opaque: VeroWhitePlus™, VeroBlackPlus™, VeroGray™, VeroBlue™, VeroCyan™, VeroMagenta™, VeroYellow™ Rubber-like: TangoPlus™, TangoBlackPlus™, TangoBlack™, TangoGray™ Transparent: VeroClear™ and RGD720 Simulated Polypropylene: Endur™ and Durus™ High Temperature Bio-compatible
<b>Digital Materials</b>	Vibrant blended colors in Rigid Opaque Translucent colored tints Rubber-like materials in a variety of Shore A values Digital ABS™ for durability, including blends with rubber Polypropylene-like materials with improved heat resistance
<b>Material Options</b>	Over 1,000
<b>Maximum Materials per Part</b>	82
<b>Support Material</b>	SUP705 non-toxic gel-like photopolymer support
<b>Maximum Build Size (XYZ)</b>	255 x 252 x 200 mm (10.0 x 9.9 x 7.9 in.)
<b>System Size and Weight</b>	87 x 120 x 73.5 cm (34.2 x 47.2 x 29 in.); 264 kg (581 lbs.) <i>Material Cabinet:</i> 33 x 117 x 64 cm (13 x 46.1 x 25.2 in.); 76 kg (168 lbs.)
<b>Resolution</b>	X-axis: 600 dpi; Y-axis: 600 dpi; Z-axis: 1600 dpi
<b>Accuracy</b>	20-85 microns for features below 50 mm; up to 200 microns for full model size
<b>Minimum Layer Thickness</b>	Horizontal build layers as fine as 16 microns (.0006 in.)
<b>Build Modes</b>	Digital material: 30-micron (.001 in.) resolution High quality: 16-micron (.0006 in.) resolution High speed: 30-micron (.001 in.) resolution
<b>Software</b>	Objet Studio™ intuitive 3D printing software
<b>Workstation Compatibility</b>	Windows® 7 or Windows® 8
<b>Network Connectivity</b>	LAN -TCP/IP
<b>Operating Conditions</b>	Temperature 18-25°C (64-77°F); relative humidity 30-70% (non-condensing)
<b>Power Requirements</b>	110-240 VAC 50/60Hz; 1.5 kW single phase
<b>Regulatory Compliance</b>	CE, FCC

### Driven by powerful PolyJet™ technology

Proven PolyJet 3D Printing is famous for smooth surfaces, fine precision and diverse material properties. It works a bit like inkjet document printing, but instead of jetting drops of ink onto paper, the print head jets microscopic layers of liquid photopolymer onto a build tray and instantly cures them with UV light. The fine layers build up to create a prototype or end-use part.

Along with the selected model material, the 3D printer also jets a gel-like support material designed to uphold overhangs. When printing is done, the nontoxic support material is easily removed with a water jet. Models can be handled and used immediately, without additional post-curing.

With its astonishingly realistic aesthetics and ability to deliver special properties such as transparency, flexibility and even biocompatibility, PolyJet 3D Printing offers a competitive edge in consumer products prototyping, precision tooling and specialized end-use parts.

Stratasys | [www.stratasys.com](http://www.stratasys.com) | [info@stratasys.com](mailto:info@stratasys.com)

7665 Commerce Way  
Eden Prairie, MN 55344  
+1 888 480-3548 (US Toll-free)  
+1 952 937-3000 (Intl.)  
+1 952 937-0070 (Fax)

2 Holtzman St.  
Science Park, P.O. Box 2496  
Rehovot 76124, Israel  
+972 74 745-4000  
+972 74 745-5000 (Fax)

©2015 Stratasys Ltd. All rights reserved. Stratasys, FDM, Fortus, Fortus 900mc, ABSi, ABS-M30, ABS-M30i, ABS-ESD7, PC-ISO, Insight, Control Center, Stratasys logo, Objet, For a 3D World, Objet Studio, Eden, Eden260, Eden260V, Eden350, Eden350V, Eden500V, Objet500 Connex1, Objet500 Connex2, Objet500 Connex3, Connex, Objet260 Connex, Connex350, Connex500, Objet1000, TangoBlack, TangoGray, TangoPlus, TangoBlackPlus, VeroBlue, VeroBlack, VeroBlackPlus, VeroClear, VeroDent, VeroGray, VeroWhite, VeroWhitePlus, VeroCyan, VeroMagenta, VeroYellow, Durus, Endur, Digital Materials, Digital ABS and PolyJet are trademarks or registered trademarks of Stratasys Ltd. and/or its subsidiaries or affiliates and may be registered in certain jurisdictions. ULTEM is a registered trademark of SABIC or affiliates. All other trademarks belong to their respective owners. MachineSS-PJ-Objet260Connex3-EN-06-15